



## Electro Plus® Marine

### Advantages:

- Intuitive user interface
  - Multiple joint capability for speedy installations
  - Integral carrying case for ease of transportation
  - One-button repeat fusion cycle for same size joints
  - Self-diagnostic error detection system
  - Automatic compensation for ambient temperature
- This complete machine includes: Fusion Power Unit, Hand Held Unit and the Cable Assembly.

### Technical Data:

- Operating temperature: 14°F (-10°C) to 113°F (+50°C)
- Input Voltage: 100-130 V AC / 200-250 V AC
- Input Frequency: 50Hz - 60Hz
- Output Voltage: 0 - 28.5 V AC
- Output Current: 0-50 Amps
- Power Consumption: 1200 Watts max.
- Power Cable Length: 5ft. (1.5m)
- Fusion Cable Length: 18ft. (5.5m)
- Remote Cable Length: 20ft. (6m)
- Dimensions (WxHxD): 22x14x10 inch
- Weight: 45lbs (20.5kg)

<u>Description</u>	<u>Code</u>
Electro Plus Marine	<b>150 000 009</b>

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>