




**ecoFIT Tee 90° reduced PE100**  
d63-250mm / SDR11

**Model:**

- Material: PE100
- Conventional butt-welding according to DVS 2207
- IR = Infrared-(IR Plus®) compatible. Choose fusion parameters: PE100



| d<br>(mm) | d1<br>(mm) | FM | Code               | PF weight<br>(kg) | L<br>(mm) | L1<br>(mm) | L2<br>(mm) | L3<br>(mm) | e<br>(mm) | e1<br>(mm) |      |
|-----------|------------|----|--------------------|-------------------|-----------|------------|------------|------------|-----------|------------|------|
| 63        | 32         | IR | <b>753 208 351</b> | 2 68 240 017      | 0.161     | 65         | 70         | 25         | 25        | 5.8        | 2,9  |
| 63        | 50         | IR | <b>753 208 352</b> | 2 68 240 017      | 0.180     | 65         | 70         | 25         | 25        | 5.8        | 4,6  |
| 75        | 32         | IR | <b>753 208 353</b> | 2 68 240 017      | 0.255     | 70         | 75         | 25         | 25        | 6.8        | 2,9  |
| 75        | 50         | IR | <b>753 208 354</b> | 2 68 240 017      | 0.265     | 70         | 75         | 25         | 25        | 6.8        | 4,6  |
| 75        | 63         | IR | <b>753 208 355</b> | 2 68 240 017      | 0.278     | 70         | 75         | 25         | 25        | 6.8        | 5,8  |
| 90        | 50         | IR | <b>753 208 357</b> | 2 68 240 017      | 0.435     | 80         | 85         | 25         | 25        | 8.2        | 4,6  |
| 90        | 63         | IR | <b>753 208 358</b> | 2 68 240 017      | 0.448     | 80         | 85         | 25         | 25        | 8.2        | 5,8  |
| 90        | 75         | IR | <b>753 208 359</b> | 2 68 240 017      | 0.462     | 80         | 85         | 25         | 25        | 8.2        | 6,8  |
| 110       | 32         | IR | <b>753 208 360</b> | 2 68 240 017      | 0.685     | 90         | 95         | 30         | 25        | 10.0       | 2,9  |
| 110       | 50         | IR | <b>753 208 361</b> | 2 68 240 017      | 0.694     | 90         | 95         | 30         | 25        | 10.0       | 4,6  |
| 110       | 63         | IR | <b>753 208 362</b> | 2 68 240 017      | 0.709     | 90         | 95         | 30         | 25        | 10.0       | 5,8  |
| 110       | 75         | IR | <b>753 208 363</b> | 2 68 240 017      | 0.717     | 90         | 95         | 30         | 25        | 10.0       | 6,8  |
| 110       | 90         | IR | <b>753 208 364</b> | 2 68 240 017      | 0.734     | 90         | 95         | 30         | 25        | 10.0       | 8,2  |
| 160       | 63         | IR | <b>753 208 371</b> | 2 68 240 017      | 2.269     | 142        | 135        | 50         | 30        | 14.6       | 5,8  |
| 160       | 75         | IR | <b>753 208 372</b> | 2 68 240 017      | 2.255     | 142        | 135        | 50         | 30        | 14.6       | 6,8  |
| 160       | 90         | IR | <b>753 208 373</b> | 2 68 240 017      | 2.317     | 142        | 135        | 50         | 30        | 14.6       | 8,2  |
| 160       | 110        | IR | <b>753 208 374</b> | 2 68 240 017      | 2.353     | 142        | 135        | 50         | 30        | 14.6       | 10,0 |
| 225       | 90         | IR | <b>753 208 388</b> | 2 68 240 017      | 4.759     | 155        | 165        | 40         | 30        | 20.5       | 8,2  |
| 225       | 110        | IR | <b>753 208 389</b> | 2 68 240 017      | 4.796     | 155        | 165        | 40         | 30        | 20.5       | 10,0 |
| 225       | 160        | IR | <b>753 208 391</b> | 2 68 240 017      | 4.854     | 155        | 165        | 40         | 30        | 20.5       | 14,6 |
| 250       | 110        |    | <b>753 221 031</b> | 2 51 301 004      | 8.120     | 228        | 197        | 140        | 37        | 22.7       | 10,0 |
| 250       | 160        |    | <b>753 221 032</b> | 2 51 301 004      | 9.700     | 229        | 219        | 117        | 60        | 22.7       | 14,6 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
info.ps@georgfischer.com Internet: <http://www.gfps.com>