


**ELGEF Plus Reducer PE100**  
**d25-630mm / SDR11 / Long version**

- Long spigot version
- PE100 **SDR11**, metric

d	d1	Code	weight	z	L	L1	e	e1
(mm)	(mm)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
25	20	<b>753 901 038</b>	0.022	115	53	52	3.0	3.0
32	20	<b>753 901 042</b>	0.027	122	55	53	3.0	3.0
32	25	<b>753 901 041</b>	0.033	122	55	53	3.0	3.0
40	20	<b>753 901 048</b>	0.043	127	56	50	3.7	3.0
40	25	<b>753 901 047</b>	0.045	128	55	50	3.7	3.0
40	32	<b>753 901 046</b>	0.047	128	55	52	3.7	3.0
50	20	<b>753 901 055</b>	0.064	147	62	50	4.6	3.0
50	25	<b>753 901 054</b>	0.069	139	62	50	4.6	3.0
50	32	<b>753 901 053</b>	0.067	140	62	54	4.6	3.0
50	40	<b>753 901 052</b>	0.079	138	62	55	4.6	3.7
63	32	<b>753 901 060</b>	0.113	150	65	53	5.8	3.0
63	40	<b>753 901 059</b>	0.122	150	65	57	5.8	3.7
63	50	<b>753 901 058</b>	0.128	150	65	62	5.8	4.6
75	40	<b>753 901 063</b>	0.185	170	72	51	6.8	3.7
75	50	<b>753 901 064</b>	0.188	170	72	65	6.8	4.6
75	63	<b>753 901 065</b>	0.209	170	72	65	6.8	5.8
90	50	<b>753 901 072</b>	0.289	190	81	61	8.2	4.6
90	63	<b>753 901 071</b>	0.316	190	81	65	8.2	5.8
90	75	<b>753 901 070</b>	0.330	190	81	72	8.2	6.8
110	63	<b>753 901 078</b>	0.487	205	85	65	10.0	5.8
110	75	<b>753 901 077</b>	0.501	205	84	72	10.0	6.8
110	90	<b>753 901 076</b>	0.549	205	85	81	10.0	8.2
125	63	<b>753 901 083</b>	0.607	214	88	65	11.4	5.8
125	75	<b>753 901 082</b>	0.667	210	89	72	11.4	6.8
125	90	<b>753 901 081</b>	0.683	211	89	81	11.4	8.2
125	110	<b>753 901 080</b>	0.775	211	90	84	11.4	10.0
140	75	<b>753 901 086</b>	0.910	237	113	77	12.7	6.8
140	90	<b>753 901 087</b>	0.954	237	114	86	12.7	8.2
140	110	<b>753 901 084</b>	0.977	232	104	93	12.7	10.0
140	125	<b>753 901 085</b>	1.078	232	102	100	12.7	11.4
160	90	<b>753 901 088</b>	1.164	244	100	81	14.6	8.2
160	110	<b>753 901 090</b>	1.239	242	100	85	14.6	10.0
160	125	<b>753 901 089</b>	1.333	240	100	89	14.6	11.4
160	140	<b>753 901 032</b>	1.522	255	110	104	14.6	12.7
180	90	<b>753 901 073</b>	1.507	245	105	81	16.4	8.2
180	110	<b>753 901 074</b>	1.833	277	124	94	16.4	10.0
180	125	<b>753 901 091</b>	1.723	258	108	92	16.4	11.4
180	140	<b>753 901 075</b>	1.976	278	124	113	16.4	12.7
180	160	<b>753 901 033</b>	1.968	255	107	102	16.4	14.6
200	140	<b>753 901 066</b>	2.326	282	123	114	18.2	12.7
200	160	<b>753 901 092</b>	2.435	252	104	120	18.2	14.6
200	180	<b>753 901 034</b>	2.724	279	124	120	18.2	16.4
225	140	<b>753 901 067</b>	2.900	295	132	115	20.5	12.7
225	160	<b>753 901 096</b>	3.100	278	120	98	20.5	14.6
225	180	<b>753 901 095</b>	3.090	297	128	120	20.5	16.4
225	200	<b>753 901 094</b>	3.380	280	124	117	20.5	18.2
250	160	<b>753 901 000</b>	3.990	309	150	97	22.7	14.6
250	180	<b>753 901 068</b>	4.299	312	150	106	22.7	16.4
250	200	<b>753 901 001</b>	4.766	327	155	115	22.7	18.2
250	225	<b>753 901 002</b>	4.950	332	130	120	22.7	20.5
280	200	<b>753 901 098</b>	5.830	347	140	115	25.4	18.2
280	225	<b>753 901 099</b>	6.112	340	140	122	25.4	20.5
280	250	<b>753 901 003</b>	6.480	320	137	133	25.4	22.7

# Data sheet

valid from: 8/21/24



d (mm)	d1 (mm)	Code	weight (kg)	z (mm)	L (mm)	L1 (mm)	e (mm)	e1 (mm)
315	200	<b>753 901 004</b>	7.522	375	170	128	28.6	18,2
315	225	<b>753 901 097</b>	7.790	375	150	123	28.6	20,5
315	250	<b>753 901 005</b>	8.360	375	150	132	28.6	22,7
315	280	<b>753 901 012</b>	8.800	375	150	144	28.6	25,4
355	250	<b>753 901 013</b>	10.140	390	165	130	32.3	22,7
355	280	<b>753 901 014</b>	10.740	390	165	139	32.3	25,4
355	315	<b>753 901 015</b>	11.590	390	165	150	32.3	28,6
400	280	<b>753 901 016</b>	13.660	415	180	139	36.4	25,4
400	315	<b>753 901 017</b>	14.490	415	180	150	36.4	28,6
400	355	<b>753 901 018</b>	15.830	420	180	165	36.4	32,3
450	280	<b>753 901 019</b>	15.420	389	195	139	40.9	25,4
450	315	<b>753 901 020</b>	16.150	390	195	150	40.9	28,6
450	355	<b>753 901 022</b>	17.240	393	195	164	40.9	32,3
450	400	<b>753 901 024</b>	18.790	395	195	179	40.9	36,4
500	315	<b>753 901 025</b>	20.780	422	212	150	45.5	28,6
500	355	<b>753 901 026</b>	21.770	424	212	164	45.5	32,3
500	400	<b>753 901 027</b>	23.270	426	212	179	45.5	36,4
500	450	<b>753 901 029</b>	25.380	428	212	195	45.5	40,9
560	355	<b>753 901 030</b>	28.420	459	230	164	50.9	32,3
560	400	<b>753 901 039</b>	29.850	461	230	179	50.9	36,4
560	450	<b>753 901 040</b>	31.870	463	230	195	50.9	40,9
560	500	<b>753 901 043</b>	34.430	466	230	212	50.9	45,5
630	400	<b>753 901 044</b>	39.400	502	250	179	57.3	36,4
630	450	<b>753 901 045</b>	41.240	503	250	195	57.3	40,9
630	500	<b>753 901 049</b>	43.700	506	250	212	57.3	45,5
630	560	<b>753 901 050</b>	47.070	506	250	230	57.3	50,9

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
info.ps@georgfischer.com Internet: <http://www.gfps.com>