


## ELGEF Plus Tee 90° reduced PE100 d25-400mm / SDR11 / Welded reducer / Long version

### Model:

- with welded reducer
- PE100 **SDR11**, metric
- Long spigot version



d (mm)	d1 (mm)	Code	weight (kg)	z1 (mm)	z (mm)	L (mm)	L1 (mm)	e (mm)	e1 (mm)
25	20	<b>753 201 002</b>	0.053		160	52	52	3.0	3.0
32	20	<b>753 201 003</b>	0.094	105	170	54	52	3.0	3.0
32	25	<b>753 201 004</b>	0.098	110	170	54	52	3.0	3.0
40	20	<b>753 201 005</b>	0.124	120	190	57	52	3.7	3.0
40	25	<b>753 201 069</b>	0.160	120	190	57	52	3.7	3.0
40	32	<b>753 201 070</b>	0.160	120	190	57	52	3.7	3.0
50	20	<b>753 201 072</b>	0.252	140	210	63	52	4.6	3.0
50	25	<b>753 201 077</b>	0.203	130	210	63	52	4.6	3.0
50	32	<b>753 201 080</b>	0.207	130	210	63	53	4.6	3.0
50	40	<b>753 201 081</b>	0.224	130	210	63	57	4.6	3.7
75	40	<b>753 201 084</b>	0.603	180	264	72	57	6.8	3.7
125	63	<b>753 201 085</b>	2.359	225	366	92	61	11.4	5.8
125	75	<b>753 201 086</b>	2.434	235	366	92	72	11.4	6.8
140	75	<b>753 201 087</b>	3.038	230	396	92	70	12.7	6.8
140	90	<b>753 201 089</b>	3.092	235	396	92	79	12.7	8.2
140	110	<b>753 201 090</b>	3.208	240	396	92	82	12.7	10.0
140	125	<b>753 201 091</b>	4.170	240	396	92	90	12.7	11.4
160	125	<b>753 201 092</b>	4.544	265	420	102	92	14.6	11.4
160	140	<b>753 201 093</b>	5.895	270	420	102	96	14.6	12.7
180	125	<b>753 201 094</b>	6.111	285	460	107	92	16.4	11.4
180	140	<b>753 201 095</b>	6.317	295	460	107	110	16.4	12.7
200	125	<b>753 201 096</b>	8.424	295	500	117	92	18.2	11.4
200	140	<b>753 201 097</b>	10.570	310	500	117	110	18.2	12.7
200	180	<b>753 201 098</b>	9.031	310	500	117	110	18.2	16.4
225	125	<b>753 201 099</b>	11.260	320	540	122	92	20.5	11.4
225	140	<b>753 201 100</b>	14.574	335	540	122	110	20.5	12.7
225	200	<b>753 201 101</b>	14.925	340	540	122	117	20.5	18.2
250	180	<b>753 201 102</b>	14.327	350	576	130	105	22.7	16.4
250	200	<b>753 201 103</b>	19.220	360	576	130	112	22.7	18.2
250	225	<b>753 201 104</b>	15.240	390	576	130	120	22.7	20.5
280	200	<b>753 201 105</b>	24.520	420	616	139	112	25.4	18.2
280	225	<b>753 201 106</b>	21.755	420	616	139	120	25.4	20.5
280	250	<b>753 201 107</b>	21.055	420	616	139	130	25.4	22.7
315	280	<b>753 201 109</b>	34.950	480	690	150	139	28.6	25.4
355	250	<b>753 201 110</b>	48.900	530	818	165	130	32.3	22.7
355	280	<b>753 201 111</b>	49.300	480	818	165	139	32.3	25.4
355	315	<b>753 201 112</b>	49.690	480	818	165	150	32.3	28.6
400	280	<b>753 201 113</b>	52.915	530	910	180	139	36.4	25.4
400	315	<b>753 201 114</b>	53.625	580	910	180	150	36.4	28.6
400	355	<b>753 201 115</b>	54.075	675	910	180	165	36.4	32.3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>