




*



PRO-FIT adaptor union PVC-U metric Rp

Model:

- Union End: Solvent cemented spigot in combination with reducing socket metric
- Union Bush: Threaded socket with parallel female thread Rp
- Gasket: O-ring EPDM code no. 748 410 005-011
- Gasket: O-ring FKM code no. 749 410 005-011 (to be ordered separately)
- Connection to plastic thread only
- Do not apply solvent-based or other sealing compounds which could damage PVC

	d (mm)	d1 (mm)	Rp (inch)	PN (bar)	EPDM Code	SP	weight (kg)
*	16	12	3/8	10	721 510 405	10	0.032
*	20	16	1/2	10	721 510 406	10	0.046
*	25	20	3/4	10	721 510 407	10	0.079
*	32	25	1	10	721 510 408	10	0.116
	40	32	1 1/4	10	721 510 409	10	0.192
	50	40	1 1/2	10	721 510 410	10	0.263
	63	50	2	10	721 510 411	10	0.496

	d (mm)	G (inch)	z1 (mm)	z2 (mm)	z3 (mm)	D (mm)	L1 (mm)	L2 (mm)
*	16	3/4	22	13	24	35	36	24
*	20	1	24	13	26	43	40	26
*	25	1 1/4	25	14	28	51	44	29
*	32	1 1/2	27	15	30	58	49	32
	40	2	31	19	35	74	57	38
	50	2 1/4	35	26	40	83	66	45
	63	2 3/4	39	33	46	100	77	56

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>