



Reducing bush PVC metric Rp

Model:

- With solvent cement spigot metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC

	d (mm)	Rp (inch)	PN (bar)	Part No.	SP	weight (kg)	z (mm)	D (mm)	L (mm)	s (mm)
*	12	¼	16	721 910 404	10	0.008	0	20	27	22
	20	¾	16	721 910 434	10	0.014	7	25	35	
	25	½	16	721 910 437	10	0.021	7	30	41	
	32	¾	16	721 910 441	10	0.032	15	35	48	
	40	1	16	721 910 446	10	0.058	20	45	56	
	50	1 ¼	16	721 910 452	10	0.097	20	55	66	
	63	1 ½	16	721 910 458	5	0.151	10	62	77	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>