



UNI-Plastgrip L PN10

Model:

- Housing, Bars and Strip insert (option): Stainless Steel W5 (1.4571) Quality

Temperature/Pressure:

- Operating Temperature EPDM: -22° F to 257° F
- Operating temperature NBR: -20°C to 80°C

Option:

- Sealing type Viton on request

Remark:

- For safe installation on PE/PP/PB pipes use insert stiffeners

OD nominal (mm) (mm)	EPDM Part No.	NBR Part No.	SP	weight (kg)
40	779 732 006	779 729 006	0	0.4
50	779 732 008	779 729 008	0	0.5
63	779 732 010	779 729 010	0	0.6
75	779 732 012	779 729 012	0	1.4
90	779 732 014	779 729 014	0	1.5
110	779 732 016	779 729 016	0	1.7
125	779 732 018	779 729 018	0	1.8
140	779 732 020	779 729 020	0	3.5
160	779 732 022	779 729 022	0	3.7

OD nominal (mm) (mm)	M	PN (bar)	WP (bar)	C max. (mm)	OD min (mm)	OD max. (mm)	d (mm)	B (mm)	H (mm)	Torque (N/m)
40	M8	10	16	15	39.0	43.0	66	60	104	25
50	M8	10	16	15	47.5	52.5	74	60	112	25
63	M8	10	16	25	58.0	64.0	85	75	125	25
75	M10	10	16	30	72.0	80.0	108	95	164	40
90	M10	10	16	30	88.0	96.0	124	95	170	40
110	M10	10	16	30	104.0	112.0	141	95	187	40
125	M10	10	16	30	122.0	130.0	158	95	202	40
140	M12	10	16	40	137.0	145.0	186	110	238	65
160	M12	10	16	40	157.0	165.0	205	110	255	65

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>