



JRGURED pressure reducing valve gunmetal

- Temperature: Max. 70°C
- Material: gunmetal, stainless steel, EPDM, plastic
- Factory setting: 600 kPa (6 bar)
- Secondary pressure: 600 - 1000 kPa (6 - 10 bar)
- Connection: manometer
- Consisting of: unions

GN (inch)	DN (mm)	JRG Code	GF Code	SP	weight (kg)
½	15	1330.240	350 732 801	1	0.730
¾	20	1330.320	350 732 901	1	1.020
1	25	1330.400	350 733 001	1	1.870
1 ¼	32	1330.480	350 733 101	1	2.700
1 ½	40	1330.560	350 733 201	1	4.590
2	50	1330.640	350 733 301	1	7.050
2 ½	65	1330.720	350 735 201	1	8.320

GN (inch)	DN (mm)	d1 R (inch)	d2 G (inch)	d3 Rp (inch)	d4 (mm)	h1 (mm)	h2 (mm)	l1 (mm)	l2 (mm)	z (mm)	⊕
½	15	½	¾	⅙	52	29	79	130	25	40	5
¾	20	¾	1	⅙	58	36	86	142	29	43	5
1	25	1	1 ¼	¼	70	52	110	167	34	50	6
1 ¼	32	1 ¼	1 ½	¼	77	64	121	196	38	60	6
1 ½	40	1 ½	1 ¾	¼	94	80	157	222	39	73	8
2	50	2	2 ¾	¼	103	98	172	268	47	88	8
2 ½	65	2 ½	3	¼	103	98	172	292	56	90	8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>