



JRGUMAT Thermostatic mixing valve gunmetal

- Temperature: Max. 90°C
- Material: Gunmetal
- Connection: Male thread

GN (inch)	DN (mm)	range (°C)	Temperature (°C)	JRG Code	GF Code	SP	weight (kg)
½	15	20 - 30	25	3400.910	350 760 511	1	0.530
½	15	30 - 45	40	3400.912	350 760 512	1	0.530
½	15	35 - 55	48	3400.914	350 760 517	1	0.530
½	15	45 - 65	55	3400.916	350 760 513	1	0.530
¾	20	20 - 30	25	3400.920	350 760 411	1	0.700
¾	20	30 - 45	40	3400.922	350 760 412	1	0.670
¾	20	35 - 55	48	3400.924	350 760 417	1	0.670
¾	20	45 - 65	55	3400.926	350 760 413	1	0.701
1	25	20 - 30	25	3400.930	350 760 311	1	0.870
1	25	30 - 45	40	3400.932	350 760 312	1	0.870
1	25	35 - 55	48	3400.934	350 760 317	1	0.910
1	25	45 - 65	55	3400.936	350 760 313	1	0.910
1 ¼	32	20 - 30	25	3400.940	350 760 211	1	1.670
1 ¼	32	30 - 45	40	3400.942	350 760 212	1	1.630
1 ¼	32	35 - 55	48	3400.944	350 760 217	1	1.590
1 ¼	32	45 - 65	55	3400.946	350 760 213	1	1.590
1 ½	40	20 - 30	25	3400.950	350 760 111	1	2.140
1 ½	40	30 - 45	40	3400.952	350 760 112	1	2.140
1 ½	40	35 - 55	48	3400.954	350 760 117	1	2.140
1 ½	40	45 - 65	55	3400.956	350 760 113	1	2.100
2	50	20 - 30	25	3400.960	350 760 011	1	3.610
2	50	30 - 45	40	3400.962	350 760 012	1	3.510
2	50	35 - 55	48	3400.964	350 760 017	1	3.510
2	50	45 - 65	55	3400.966	350 760 013	1	3.510

GN (inch)	DN (mm)	d2 G (inch)	d3 G (inch)	h1 (mm)	h2 (mm)	h3 (mm)	l (mm)	l1 (mm)	l2 (mm)	⊙
½	15	1 ½			47	35	90	35	55	5
½	15	1 ½			47	35	90	35	55	5
½	15	1 ½			47	35	90	35	55	5
½	15	1 ½			47	35	90	35	55	5
¾	20	1 ½	½	32	49	40	100	40	60	5
¾	20	1 ½	½	32	49	40	100	40	60	5
¾	20	1 ½	½	32	49	40	100	40	60	5
¾	20	1 ½	½	32	49	40	100	40	60	5
1	25	1 ½	¾	36	51	43	110	43	67	5
1	25	1 ½	¾	36	51	43	110	43	67	5
1	25	1 ½	¾	36	51	43	110	43	67	5
1	25	1 ½	¾	36	51	43	110	43	67	5
1 ¼	32	2	¾	41	75	52	130	52	78	8
1 ¼	32	2	¾	41	75	52	130	52	78	8
1 ¼	32	2	¾	41	75	52	130	52	78	8
1 ¼	32	2	¾	41	75	52	130	52	78	8
1 ½	40	2 ½	¾	50	77	58	150	58	92	8
1 ½	40	2 ½	¾	50	77	58	150	58	92	8
1 ½	40	2 ½	¾	50	77	58	150	58	92	8
1 ½	40	2 ½	¾	50	77	58	150	58	92	8
2	50	2 ¾	¾	60	85	70	180	70	110	8
2	50	2 ¾	¾	60	85	70	180	70	110	8
2	50	2 ¾	¾	60	85	70	180	70	110	8
2	50	2 ¾	¾	60	85	70	180	70	110	8

Data sheet

valid from: 8/27/24



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>