



JRG Sanipex MT Multilayer pipe PE-Xc

In bars, multilayer pipe (PE-X/AL/PEX), according DVGW W542 and EN ISO 21003, inner pex pipe (white) and outer pex coating (black) made of cross linked polyethylen (PE-X), support pipe in aluminium, butt welded, for drinking water 70°C/10 bar, heating max.95°C and compressed air installations (dry and oil free)

d (mm)	DN (mm)	JRG Code	GF Code	SP	weight (kg)	l (m)	s (mm)
16	12	4600.016	351 616 702	25	0.675	5	2.25
20	15	4600.020	351 620 702	16	0.194	5	2.50
26	20	4600.026	351 626 702	9	0.288	5	3.00
32	25	4600.032	351 632 702	7	0.398	5	3.00
40	32	4600.040	351 640 902	4	0.606	5	3.50
50	40	4600.050	351 650 902	5	0.904	5	4.00
63	50	4600.063	351 663 902	4	1.356	5	4.50
16	12	4600.316	351 616 712	25	0.405	3	2.25
20	15	4600.320	351 620 712	16	0.555	3	2.50
26	20	4600.326	351 626 712	9	0.855	3	3.00
32	25	4600.332	351 632 712	7	1.179	3	3.00
40	32	4600.340	351 640 912	4	0.605	3	3.50

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>