



JRG Sanipex MT Transition gunmetal With push-in connection

- Description: for stainless steel / copper pipes
- Temperature: Max. 90°C
- Material: gunmetal, PPSU
- Connection: push-in system sudoFIT

d	DN	JRG	GF	SP	weight	d1	d2	l1	z1
(mm)	(mm)	Code	Code		(kg)	(mm)	(mm)	(mm)	(mm)
16 - 12	10	4714.098	351 060 500	5	0.065	16	12	55	16
16 - 15	12	4714.100	351 060 501	1	0.075	16	15	62	21
20 - 18	15	4714.104	351 060 511	1	0.125	20	18	76	24
20 - 22	15	4714.105	351 060 516	1	0.140	20	22	82	25
26 - 22	20	4714.106	351 060 521	1	0.140	26	22	75	15
32 - 28	25	4714.108	351 060 531	1	0.245	32	28	93	14
40 - 35	32	4714.110	351 060 541	1	0.380	40	35	107	16

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>