



JRG Sanipex MT LegioStop Y-type valve gunmetal

- Description: Free of water pockets and maintenance free top, non rising handwheel with optical position indicator
- Temperature: Max. 90°C
- Material: gunmetal, stainless steel, EPDM, plastic
- Connection: JRG Sanipex MT
- Consisting of: grinded valve stem, valve seat

d (mm)	DN (mm)	JRG Code	GF Code	SP	weight (kg)
16	12	5222.016	350 895 732	1	0.360
20	15	5222.020	350 895 733	1	0.390
26	20	5222.026	350 895 734	1	0.590
32	25	5222.032	350 895 735	1	0.950
40	32	5222.040	350 895 736	1	1.360
50	40	5222.050	351 650 970	1	2.160
63	50	5222.063	351 663 970	1	3.380

d (mm)	DN (mm)	d1 (mm)	d2 G (inch)	d3 Rp (inch)	d4 (mm)	h (mm)	l1 (mm)	l2 (mm)	z1 (mm)	z2 (mm)	⊙
16	12	16	½	¼	53	87	115	133	28	50	6
20	15	20	½	¼	53	87	122	137	27	51	6
26	20	26	¾	¼	53	105	148	160	27	63	6
32	25	32	1	¼	60	117	178	182	28	75	6
40	32	40	1 ¼	¼	70	130	212	212	37	92	6
50	40	50	1 ½	¼	90	175	256	245	46	108	6
63	50	63	2	¼	90	196	315	287	55	134	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>