



## JRG Sanipex MT Ball valve, PN 10

- Material: gunmetal, plastic
- Temperature: max. -20°C / +95°C (water, compressed air, vacuum)
- Connection: cone grip unions

d (mm)	DN (mm)	JRG Part No.	GF Part No.	SP	weight (kg)	d1 (mm)	h (mm)	l (mm)	l1 (mm)	z1 (mm)	z2 (mm)
16	12	<b>6041.016</b>	<b>351 616 310</b>	1	0.230	16	45	94	84	28	28
20	15	<b>6041.020</b>	<b>351 620 310</b>	1	0.308	20	49	109	84	31	31
26	20	<b>6041.026</b>	<b>351 626 310</b>	1	0.543	26	63	131	125	37	37
32	25	<b>6041.032</b>	<b>351 632 310</b>	1	0.933	32	71	158	125	42	42
40	32	<b>6041.040</b>	<b>351 640 310</b>	1	1.547	40	75	186	125	49	49

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>