


## JRG LegioTherm 2T circulation valve gunmetal with controller

- Temperature: Max. 90°C
- Material: gunmetal, stainless steel, EPDM
- Factory setting: 57°C (adjustable 0 - 90°C) thermal desinfection 70°C (adjustable 60 - 90°C)
- Connection: male thread (for union connection with flat gasket)

DN (mm)	JRG Code	GF Code	SP	weight (kg)
15	<b>9910.015</b>	<b>351 110 550</b>	1	0.820
20	<b>9910.020</b>	<b>351 110 590</b>	1	1.050
25	<b>9910.025</b>	<b>351 110 630</b>	1	1.400



DN (mm)	d1 G (inch)	d2 G (inch)	d3 Rp (inch)	l1 (mm)	l2 (mm)	l3 (mm)	l4 (mm)	b (mm)	h1 (mm)	h2 (mm)	⊙
15	¾	½	¼	75	6	24	173	90	162	50	6
20	1	¾	¼	87	7	24	206	92	169	54	6
25	1 ¼	1	¼	99	8	24	233	100	179	56	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>