



COOL-FIT 4.0 Pipe d32-d450

Model:

- Pre-insulated PE100 **SDR11/17**, metric
- Insulation made from PUR foam
- Outer jacket impact and UV resistant. Color: Black
- Length: 5m (16.4 ft)
- extremos pelados para electrofusión
- Pre-insulated PE100 **SDR17**, metric
- Outer jacket impact and UV resistant. Color: Black
- Insulated length: 5m
- Insulation made from PUR
- Length: 5.9m

d/D (mm)	DN (mm)	SDR	PN (bar)	Code	weight (kg/m)	di (mm)	L (mm)	L1 (mm)	closest inch (inch)	x (mm)
32/90	25	11	16	738 173 108	1.411	26.2	5000	36	1	
40/110	32	11	16	738 173 109	2.054	32.6	5000	40	1 ¼	
50/110	40	11	16	738 173 110	2.221	40.8	5000	44	1 ½	
63/125	50	11	16	738 173 111	2.987	51.4	5000	48	2	
75/140	65	11	16	738 173 112	3.757	61.4	5000	55	2 ½	
90/160	80	11	16	738 173 113	4.819	73.6	5000	62	3	
110/180	100	11	16	738 173 114	6.200	90.0	5000	72	4	
160/250	150	17	10	738 173 117	9.921	141.0	5000	90	6	
225/315	200	17	10	738 173 120	16.620	198.2	5000	110	8	
250/355	250	17	10	738 173 021	18.180	220.4	5900	123	10	123
280/400	250	17	10	738 173 022	22.640	246.8	5900	126	10	126
315/450	300	17	10	738 173 023	28.510	277.6	5900	133	12	133
355/500	350	17	10	738 173 024	35.350	312.8	5900	148	14	145
400/560	400	17	10	738 173 125	44.070	352.6	5900	150	16	147
450/630	450	17	10	738 173 126	55.490	396.6	5900	165	18	163

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>