




**COOL-FIT 4.0 Elbow 90°
d32-d225**

Model:

- Pre-insulated PE100 **SDR11**, metric
- Insulation made from PUR foam
- Outer jacket impact and UV resistant. Color: Black
- Electrofusion Fitting with integrated sealing lip, for a water and vapor tight seal



d/D (mm)	PN (bar)	Code	weight (kg)	D1 (mm)	L (mm)	L1 (mm)	z (mm)	closest inch (inch)	Type
32/90	16	738 103 108	0.255	97	81	36	20	1	A
40/110	16	738 103 109	0.177	117	88	40	23	1 ¼	A
50/110	16	738 103 110	0.250	117	99	44	30	1 ½	A
63/125	16	738 103 111	0.372	132	107	48	34	2	A
75/140	16	738 103 112	0.800	147	120	55	40	2 ½	A
90/160	16	738 103 113	1.500	168	150	62	63	3	A
110/180	16	738 103 114	1.950	188	174	72	77	4	A
160/250	16	738 103 117	5.200	258	220	90	105	6	A
225/315	16	738 103 120	12.400	324	345	110	210	8	A

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>