




## PVC-C Ball valve type 546 & 546 Pro Sanipex MT

### Model:

- Material: CPVC
- For easy installation and removal
- Ball seats PTFE
- Integrated stainless steel mounting inserts
- z-dimension, valve end and union nut are not compatible with type 346

### Option:

- Individual configuration of the valve
- Multifunctional module with integrated limit switches
- Pneumatic or electric actuators from GF



Rp (inch)	d (mm)	DN (mm)	PN (bar)	Cv-value (l/min)	weight (kg)	SP	EPDM Code	SP	weight (kg)	FKM Code
3/8	16	10	16	70	0.115	1	<b>700 247 221</b>	1	0.115	<b>700 247 321</b>
1/2	20	15	16	185	0.115	1	<b>700 247 222</b>	1	0.115	<b>700 247 322</b>
3/4	26	20	16	350	0.178	1	<b>700 247 223</b>	1	0.178	<b>700 247 323</b>
1	32	25	16	700	0.253	1	<b>700 247 224</b>	1	0.253	<b>700 247 324</b>
1 1/4	40	32	16	1000	0.442	1	<b>700 247 225</b>	1	0.442	<b>700 247 325</b>
1 1/2	50	40	16	1600	0.607	1	<b>700 247 226</b>	1	0.607	<b>700 247 326</b>
2	63	50	16	3100	1.117	1	<b>700 247 227</b>	1	1.118	<b>700 247 327</b>

Rp (inch)	D (mm)	H (mm)	H1 (mm)	L (mm)	L1 (mm)	L2 (mm)	Z (mm)	L4 (mm)	L5 (mm)	L6 (mm)
3/8	50	57	27	146	77	56	108	25	32	45
1/2	50	57	27	160	77	56	112	25	32	45
3/4	58	67	30	191	97	65	133	25	39	58
1	68	73	36	215	97	71	141	25	39	58
1 1/4	84	90	44	257	128	85	169	45	54	74
1 1/2	97	97	51	297	128	89	197	45	54	74
2	124	116	64	363	152	101	237	45	66	87

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>